



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



## ORION BASE RED TONERS OB-5XX S275-OB-5XX

Date of compilation: 2023-01-13

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name

Alternative number(s)

#### ORION BASE RED TONERS

OB-500 ORION BASE GLOSS RED , OB-510 ORION BASE REDDISH MAROON, OB-520 ORION BASE ROYAL MAROON, OB-530 ORION BASE DARK MAROON, OB-535 ORION BASE CLEAN MAROON, OB-540 ORION BASE OXIDE RED, OB-550 ORION BASE REDDISH GOLD, OB-560 ORION BASE PURPLISH RED, OB-570 ORION BASE TONER RED, OB-575 ORION BASE CHERRY RED, OB-580 ORION BASE CLEAN RED, OB-590 ORION BASE MAGENTA RED

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

General use

#### 1.3 Details of the supplier of the safety data sheet

Orion Automotive Finishes LLC  
PO Box 34 - 1959 Kings Hwy  
Swedesboro, NJ  
08085, USA

Telephone: +1844 578 1750  
Telefax: +1 512 793 9796  
Website  
[www.orionautomotivefinishes.com](http://www.orionautomotivefinishes.com)

#### 1.4 Emergency telephone number

INFOTRAC [www.infotrac.net](http://www.infotrac.net)  
US & Canada: +1 800 535 5053  
International: +1 352 323 3500 .

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1O	Acute toxicity (oral)	5	Acute Tox. 5	H303
3.1D	Acute toxicity (dermal)	5	Acute Tox. 5	H313
3.1I	Acute toxicity (inhal.)	5	Acute Tox. 5	H333



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.2	Skin corrosion/irritation	3	Skin Irrit. 3	H316
3.3	Serious eye damage/eye irritation	2B	Eye Irrit. 2B	H320
3.7	Reproductive toxicity	2	Repr. 2	H361d
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1A	Hazardous to the aquatic environment - acute hazard	3	Aquatic Acute 3	H402
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

## 2.2 Label elements

### Labeling

- Signal word **danger**

- Pictograms

GHS02, GHS07, GHS08



- Hazard statements

H226	Flammable liquid and vapour.
H303+H313+H333	May be harmful if swallowed, in contact with skin or if inhaled.
H304	May be fatal if swallowed and enters airways.
H316	Causes mild skin irritation.
H320	Causes eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### - Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

### 2.3 Other hazards

of no significance

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### 3.2.1 Description of the mixture

Name of substance	Identifier	Wt%
BUTYL ACETATE	CAS No 123-86-4	10 - < 25
XILENE	CAS No 1330-20-7	10 - < 25
RESINA	CAS No Propietario	10 - < 25
TOLUENE	CAS No 108-88-3	10 - < 25



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

Name of substance	Identifier	Wt%
RESINA	CAS No Propietario	5 – < 10
METHYL ISOBUTYL KETONE	CAS No 108-10-1	1 – < 5
1-METHOXYPROPAN-2-OL	CAS No 107-98-2	1 – < 5
ACETYLTRIBUTYL CITRATE	CAS No 77-90-7	1 – < 5
ADITIVO HUMECTANTE Y DISPERSANTE	CAS No Propietario	1 – < 5
ETHYL ACETATE	CAS No 141-78-6	1 – < 5
RESINA	CAS No 9004-36-8	1 – < 5
PASTA DE CERA SINTETICA	CAS No Propietario	1 – < 5
PIGMENTO QUINACRIDONE	CAS No 1047-16.1	< 1

For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Co un- try	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/ m <sup>3</sup> ]	STEL [ppm]	STEL [mg/ m <sup>3</sup> ]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Source
US	PROPYLENE GLYCOL MONO-METHYL ETHER	107-98-2	PEL (CA)	100	360	150	540				Cal/OSHA PEL
US	PROPYLENE GLYCOL MONO-METHYL ETHER	107-98-2	REL	100 (10 h)	360 (10 h)	150	540				NIOSH REL
US	HEXONE	108-10-1	REL	50 (10 h)	205 (10 h)	75	300				NIOSH REL
US	HEXONE (METHYL ISOBUTYL KETONE)	108-10-1	PEL	100	410						29 CFR 1910.1000
US	METHYL ISOBUTYL KETONE (HEX-ONE)	108-10-1	PEL (CA)	50	205	75	300				Cal/OSHA PEL
US	TOLUENE	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	TOLUENE	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1000
US	TOLUENE (TOLU-OL)	108-88-3	PEL (CA)	10	37	150	560	500			Cal/OSHA PEL
US	N-BUTYL ACET-ATE	123-86-4	PEL (CA)	150	710	200	950				Cal/OSHA PEL
US	N-BUTYL ACET-ATE	123-86-4	REL	150 (10 h)	710 (10 h)	200	950				NIOSH REL
US	N-BUTYL ACET-ATE	123-86-4	PEL	150	710						29 CFR 1910.1000
US	XYLENE, MIX-TURE OF ISO-MERS	1330-20-7	PEL	100	435						29 CFR 1910.1000



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Occupational exposure limit values (Workplace Exposure Limits)

Co un- try	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/ m <sup>3</sup> ]	STEL [ppm]	STEL [mg/ m <sup>3</sup> ]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Source
US	XYLENE (DI-METHYLBENZENE)	1330-20-7	PEL (CA)	100	435	150	655	300			Cal/OSHA PEL
US	CARBON BLACK IN PRESENCE OF POLYCYCLIC AROMATIC HYDROCARBONS (PAHS)	1333-86-4	REL		0.1 (10 h)					PAHs, appx-A, appx-C	NIOSH REL
US	CARBON BLACK	1333-86-4	PEL (CA)		3.5						Cal/OSHA PEL
US	CARBON BLACK	1333-86-4	PEL		3.5						29 CFR 1910.1000
US	CARBON BLACK	1333-86-4	REL		3.5 (10 h)					Appx-A, appx-C	NIOSH REL
US	ETHYL ACETATE	141-78-6	PEL (CA)	400	1,400						Cal/OSHA PEL
US	ETHYL ACETATE	141-78-6	REL	400 (10 h)	1,400 (10 h)						NIOSH REL
US	ETHYL ACETATE	141-78-6	PEL	400	1,400						29 CFR 1910.1000
US	GRAPHITE	7782-42-5	PEL (CA)		2.5					Natural, r	Cal/OSHA PEL
US	GRAPHITE	7782-42-5	REL		2.5 (10 h)					Natural, r	NIOSH REL
US	GRAPHITE	7782-42-5	PEL	529.5						Part ml, r, natural	29 CFR 1910.1000
US	GRAPHITE	7782-42-5	REL							Synthetic, appx-D	NIOSH REL





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Occupational exposure limit values (Workplace Exposure Limits)

Co un- try	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/ m <sup>3</sup> ]	STEL [ppm]	STEL [mg/ m <sup>3</sup> ]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Source
US	GRAPHITE	7782-42-5	PEL (CA)		10					Syn- thet- ic, dust	Cal/OSHA PEL
US	GRAPHITE	7782-42-5	PEL		15					Syn- thet- ic, i, dust	29 CFR 1910.1000
US	GRAPHITE	7782-42-5	PEL (CA)		5					Syn- thet- ic, r	Cal/OSHA PEL
US	GRAPHITE	7782-42-5	PEL		5					Syn- thet- ic, r, dust	29 CFR 1910.1000

#### Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
appx-C	Appendix C - Supplementary Exposure Limits
appx-D	see Appendix D - Substances with No Established RELs
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
i	inhalable fraction
natural	natural
PAHs	as polycyclic aromatic hydrocarbons (PAHs)
part/ml	particles/ml
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
synthetic	synthetic
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components of the mixture

NAME OF SUBSTANCE	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
XILENE	1330-20-7	DNEL	221 mg/m <sup>3</sup>	Human, inhalat- ory	Worker (in- dustry)	Chronic - systemic ef- fects
XILENE	1330-20-7	DNEL	442 mg/m <sup>3</sup>	Human, inhalat- ory	Worker (in- dustry)	Acute - sys- temic effects
XILENE	1330-20-7	DNEL	221 mg/m <sup>3</sup>	Human, inhalat- ory	Worker (in- dustry)	Chronic - loc- al effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Relevant DNELs of components of the mixture

NAME OF SUBSTANCE	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
XILENE	1330-20-7	DNEL	442 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - local effects
XILENE	1330-20-7	DNEL	212 mg/kg bw/day	Human, dermal	Worker (in-dustry)	Chronic - systemic ef-fects
TOLUENE	108-88-3	DNEL	192 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Chronic - systemic ef-fects
TOLUENE	108-88-3	DNEL	384 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - sys-temic effects
TOLUENE	108-88-3	DNEL	192 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Chronic - loc-al effects
TOLUENE	108-88-3	DNEL	384 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - local effects
TOLUENE	108-88-3	DNEL	384 mg/kg bw/day	Human, dermal	Worker (in-dustry)	Chronic - systemic ef-fects
1-METHOXYPROPAN-2-OL	107-98-2	DNEL	369 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Chronic - systemic ef-fects
1-METHOXYPROPAN-2-OL	107-98-2	DNEL	553.5 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - sys-temic effects
1-METHOXYPROPAN-2-OL	107-98-2	DNEL	553.5 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - local effects
1-METHOXYPROPAN-2-OL	107-98-2	DNEL	183 mg/kg bw/day	Human, dermal	Worker (in-dustry)	Chronic - systemic ef-fects
ETHYL ACETATE	141-78-6	DNEL	734 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Chronic - systemic ef-fects
ETHYL ACETATE	141-78-6	DNEL	1,468 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - sys-temic effects
ETHYL ACETATE	141-78-6	DNEL	734 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Chronic - loc-al effects
ETHYL ACETATE	141-78-6	DNEL	1,468 mg/m <sup>3</sup>	Human, inhalat-ory	Worker (in-dustry)	Acute - local effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Relevant DNELs of components of the mixture

NAME OF SUBSTANCE	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ETHYL ACETATE	141-78-6	DNEL	63 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects
METHYL ISOBUTYL KETONE	108-10-1	DNEL	83 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - systemic effects
METHYL ISOBUTYL KETONE	108-10-1	DNEL	208 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Acute - systemic effects
METHYL ISOBUTYL KETONE	108-10-1	DNEL	83 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - local effects
METHYL ISOBUTYL KETONE	108-10-1	DNEL	208 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Acute - local effects
METHYL ISOBUTYL KETONE	108-10-1	DNEL	11.8 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects
ACETYLTRIBUTYL CITRATE	77-90-7	DNEL	7.04 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - systemic effects
ACETYLTRIBUTYL CITRATE	77-90-7	DNEL	2 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects
PIGMENTO QUINACRIDONE	1047-16.1	DNEL	7.76 mg/m <sup>3</sup>	Human, inhalatory	Worker (industry)	Chronic - systemic effects
PIGMENTO QUINACRIDONE	1047-16.1	DNEL	3.33 mg/kg bw/day	Human, dermal	Worker (industry)	Chronic - systemic effects

### Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
XILENE	1330-20-7	PNEC	0.327 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
XILENE	1330-20-7	PNEC	0.327 mg/l	Aquatic organisms	Marine water	Short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
XILENE	1330-20-7	PNEC	6.58 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
XILENE	1330-20-7	PNEC	12.46 mg/kg	Aquatic organisms	Freshwater sediment	Short-term (single instance)
XILENE	1330-20-7	PNEC	12.46 mg/kg	Aquatic organisms	Marine sediment	Short-term (single instance)
XILENE	1330-20-7	PNEC	2.31 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
TOLUENE	108-88-3	PNEC	0.68 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
TOLUENE	108-88-3	PNEC	0.68 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
TOLUENE	108-88-3	PNEC	13.61 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
TOLUENE	108-88-3	PNEC	16.39 mg/kg	Aquatic organisms	Freshwater sediment	Short-term (single instance)
TOLUENE	108-88-3	PNEC	16.39 mg/kg	Aquatic organisms	Marine sediment	Short-term (single instance)
TOLUENE	108-88-3	PNEC	2.89 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
1-METHOXYPROPAN-2-OL	107-98-2	PNEC	10 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
1-METHOXYPROPAN-2-OL	107-98-2	PNEC	1 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
1-METHOXYPROPAN-2-OL	107-98-2	PNEC	100 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
1-METHOXYPROPAN-2-OL	107-98-2	PNEC	52.3 mg/kg	Aquatic organisms	Freshwater sediment	Short-term (single instance)
1-METHOXYPROPAN-2-OL	107-98-2	PNEC	5.2 mg/kg	Aquatic organisms	Marine sediment	Short-term (single instance)
1-METHOXYPROPAN-2-OL	107-98-2	PNEC	4.59 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
ETHYL ACETATE	141-78-6	PNEC	0.24 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
ETHYL ACETATE	141-78-6	PNEC	0.024 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
ETHYL ACETATE	141-78-6	PNEC	650 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
ETHYL ACETATE	141-78-6	PNEC	1.15 mg/kg	Aquatic organisms	Freshwater sediment	Short-term (single instance)
ETHYL ACETATE	141-78-6	PNEC	0.115 mg/kg	Aquatic organisms	Marine sediment	Short-term (single instance)
ETHYL ACETATE	141-78-6	PNEC	0.148 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
METHYL ISOBUTYL KETONE	108-10-1	PNEC	0.6 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
METHYL ISOBUTYL KETONE	108-10-1	PNEC	0.06 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
METHYL ISOBUTYL KETONE	108-10-1	PNEC	27.5 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
METHYL ISOBUTYL KETONE	108-10-1	PNEC	8.27 mg/kg	Aquatic organisms	Freshwater sediment	Short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
METHYL ISOBUTYL KETONE	108-10-1	PNEC	0.83 mg/kg	Aquatic organisms	Marine sediment	Short-term (single instance)
METHYL ISOBUTYL KETONE	108-10-1	PNEC	1.3 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
ACETYLRIBUTYL CITRATE	77-90-7	PNEC	0.022 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
ACETYLRIBUTYL CITRATE	77-90-7	PNEC	0.002 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
ACETYLRIBUTYL CITRATE	77-90-7	PNEC	100 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)
ACETYLRIBUTYL CITRATE	77-90-7	PNEC	41.5 mg/kg	Aquatic organisms	Freshwater sediment	Short-term (single instance)
ACETYLRIBUTYL CITRATE	77-90-7	PNEC	4.15 mg/kg	Aquatic organisms	Marine sediment	Short-term (single instance)
ACETYLRIBUTYL CITRATE	77-90-7	PNEC	8.29 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
PIGMENTO QUINACRIDONE	1047-16.1	PNEC	0.13 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)

## 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Skin protection

#### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	ROJO
Odor	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	128 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined
Flash point	26 °C at 1,013 hPa
Auto-ignition temperature	238 °C
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Solubility(ies)	not determined



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	1,330 Pa at 20 °C
----------------	-------------------

### Density and/or relative density

Density	0.99 – 1.1 g/cm <sup>3</sup> at 25 °C
---------	---------------------------------------

Particle characteristics	no data available
--------------------------	-------------------

## 9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

### Other safety characteristics

Solvent content	55 – 60 %
Solid content	40 – 45 %
Temperature class (USA, acc. to NEC 500)	T2C (maximum permissible surface temperature on the equipment: 230°C)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

##### Acute toxicity

May be harmful if swallowed. May be harmful in contact with skin. May be harmful if inhaled.

##### - Acute toxicity estimate (ATE)

Oral	2,256 mg/kg
Dermal	2,940 mg/kg
Inhalation: vapor	31.62 mg/l/4h

##### Skin corrosion/irritation

Causes mild skin irritation.

##### Serious eye damage/eye irritation

Causes eye irritation.

##### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
METHYL ISOBUTYL KETONE	108-10-1	2B	
XILENE	1330-20-7	3	
TOLUENE	108-88-3	3	

#### Legend

2B Possibly carcinogenic to humans  
3 Not classifiable as to carcinogenicity in humans

#### Reproductive toxicity

Suspected of damaging the unborn child.

#### Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
BUTYL ACETATE	123-86-4	LC50	18 mg/l	Fish	96 h
BUTYL ACETATE	123-86-4	EC50	18 mg/l	Fish	96 h
BUTYL ACETATE	123-86-4	ErC50	392 mg/l	Algae	48 h
XILENE	1330-20-7	LC50	8.4 mg/l	Fish	96 h
XILENE	1330-20-7	EC50	4.9 mg/l	Algae	72 h
XILENE	1330-20-7	ErC50	4.7 mg/l	Algae	72 h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
TOLUENE	108-88-3	LC50	5.5 mg/l	Fish	96 h
RESINA	Propietario	EC50	100 mg/l	Not specified	48 h
1-METHOXYPROPAN-2-OL	107-98-2	LC50	<10,000 mg/l	Fish	96 h
ETHYL ACETATE	141-78-6	LC50	230 mg/l	Fish	96 h
ETHYL ACETATE	141-78-6	EC50	220 mg/l	Fish	96 h
METHYL ISOBUTYL KETONE	108-10-1	LC50	>179 mg/l	Fish	96 h
METHYL ISOBUTYL KETONE	108-10-1	EC50	>200 mg/l	Aquatic invertebrates	48 h
ACETYLTRIBUTYL CITRATE	77-90-7	LC50	<60 mg/l	Fish	96 h
ACETYLTRIBUTYL CITRATE	77-90-7	ErC50	74.4 mg/l	Algae	72 h
ACETYLTRIBUTYL CITRATE	77-90-7	EC50	11.5 mg/l	Algae	72 h
PIGMENTO QUINACRIDONE	1047-16.1	LL50	11 mg/l	Fish	48 h
PIGMENTO QUINACRIDONE	1047-16.1	LC50	7.22 mg/l	Fish	48 h
PIGMENTO QUINACRIDONE	1047-16.1	EL50	24 mg/l	Aquatic invertebrates	48 h
PIGMENTO QUINACRIDONE	1047-16.1	EC50	20 mg/l	Aquatic invertebrates	48 h
PIGMENTO QUINACRIDONE	1047-16.1	ErC50	29.6 mg/l	Algae	72 h

### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
BUTYL ACETATE	123-86-4	EC50	34.2 mg/l	Aquatic invertebrates	21 d
BUTYL ACETATE	123-86-4	LC50	43.5 mg/l	Aquatic invertebrates	21 d
BUTYL ACETATE	123-86-4	ErC50	335 mg/l	Algae	24 h



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
XILENE	1330-20-7	EL50	2.9 mg/l	Aquatic invertebrates	21 d
XILENE	1330-20-7	ErC50	4.36 mg/l	Algae	73 h
XILENE	1330-20-7	EC50	2.2 mg/l	Algae	73 h
TOLUENE	108-88-3	LC50	3.78 mg/l	Aquatic invertebrates	2 d
TOLUENE	108-88-3	EC50	3.23 mg/l	Aquatic invertebrates	7 d
1-METHOXYPROPAN-2-OL	107-98-2	ErC50	>1,000 mg/l	Algae	7 d
ETHYL ACETATE	141-78-6	EC50	2,306 mg/l	Aquatic invertebrates	24 h
METHYL ISOBUTYL KETONE	108-10-1	EC50	3,623 mg/l	Aquatic invertebrates	24 h
ACETYLTRIBUTYL CITRATE	77-90-7	EC50	>1 mg/l	Aquatic invertebrates	24 h
PIGMENTO QUINACRIDONE	1047-16.1	LL50	>20 mg/l	Fish	24 h
PIGMENTO QUINACRIDONE	1047-16.1	LC50	>13.8 mg/l	Fish	24 h
PIGMENTO QUINACRIDONE	1047-16.1	EL50	28.3 mg/l	Aquatic invertebrates	24 h
PIGMENTO QUINACRIDONE	1047-16.1	EC50	23.8 mg/l	Aquatic invertebrates	24 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
BUTYL ACETATE	123-86-4		2.3 (pH value: 7, 25 °C)	
XILENE	1330-20-7	>5.5 – <12.2	3.2 (pH value: 7, 20 °C)	
TOLUENE	108-88-3	90	2.73 (pH value: 7, 20 °C)	



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
1-METHOXYPROPAN-2-OL	107-98-2		<1 (pH value: 6.8, 20 °C)	
ETHYL ACETATE	141-78-6	30	0.68 (pH value: 7, 25 °C)	
METHYL ISOBUTYL KETONE	108-10-1		1.9 (pH value: 6.7)	
ACETYLTRIBUTYL CITRATE	77-90-7	31.57	4.86 (pH value: 7.1, 40 °C)	
PIGMENTO QUINACRIDONE	1047-16.1	2	>2.05 – <13.25	

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Information on this property is not available.

#### 12.7 Other adverse effects

Data are not available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.




# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### SECTION 14: Transport information

<b>14.1 UN number</b>	1263
DOT	UN 1263
IMDG-Code	UN 1263
ICAO-TI	UN 1263
<b>14.2 UN proper shipping name</b>	PAINT
DOT	Paint
IMDG-Code	PAINT
ICAO-TI	Paint
<b>14.3 Transport hazard class(es)</b>	
DOT	3
IMDG-Code	3
ICAO-TI	3
<b>14.4 Packing group</b>	
DOT	III
IMDG-Code	III
ICAO-TI	III
<b>14.5 Environmental hazards</b>	none
<b>14.6 Special precautions for user</b>	there is no additional information
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
<b>Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information</b>	
Particulars in the shipper's declaration	UN1263, Paint, 3, III
Reportable quantity (RQ)	849.9 lbs (385.8 kg) (XILENE) (TOLUENE)
Danger label(s)	3
	
Special provisions (SP)	B1, B52, IB3, T2, TP1, TP29
ERG No	128



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
METHYL ISOBUTYL KETONE	108-10-1		1986-12-31
XILENE	1330-20-7		1986-12-31
TOLUENE	108-88-3		1986-12-31

##### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
METHYL ISOBUTYL KETONE	108-10-1		3 4	5000 (2270)
ETHYL ACETATE	141-78-6		4	5000 (2270)
BUTYL ACETATE	123-86-4		1	5000 (2270)
XILENE	1330-20-7		1 3 4	100 (45,4)
TOLUENE	108-88-3		1 2 3 4	1000 (454)

##### Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

##### Clean Air Act

none of the ingredients are listed



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

### Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
METHYL ISOBUTYL KETONE	108-10-1		F3 R1
1-METHOXYPROPAN-2-OL	107-98-2		F3
ETHYL ACETATE	141-78-6		F3
BUTYL ACETATE	123-86-4		F3
XILENE	1330-20-7		F3
TOLUENE	108-88-3		TE F3

#### Legend

F3 Flammable - Third Degree  
R1 Reactive - First Degree  
TE Teratogenic

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
Methyl isobutyl ketone	108-10-1		Cancer
Methyl isobutyl ketone (MIBK)	108-10-1		Develop- mental
Toluene	108-88-3		Develop- mental

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure
Health	3	Major injury likely unless prompt action is taken and medical treatment is given
Flammability	3	Material that can be ignited under almost all ambient temperature conditions





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

Category	Rating	Description
Physical hazard	0	Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	Material that can be ignited under almost all ambient temperature conditions
Health	3	Material that, under emergency conditions, can cause serious or permanent injury
Instability	0	Material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
US	TSCA	Not all ingredients are listed

#### Legend

TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
29 CFR 1910.1200 App D	OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200 - Appendix D - Safety Data Sheets
49 CFR US DOT	49 CFR U.S. Department of Transportation
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
Log KOW	n-Octanol/water
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
Ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## ORION BASE RED TONERS OB-5XX

Date of compilation: 2022-02-01

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
TWA	Time-weighted average
VPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H316	Causes mild skin irritation.
H320	Causes eye irritation.
H333	May be harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.